

GULFRACER™ GOLD
range of
sealed maintenance
free batteries
by Reem.



Extraordinary Batteries

- Extensive & Global range of Automotive batteries.
- Desert proof maintenance free battery, withstands the harshest conditions.
- Full Frame Technology guarantees reliable start & longer life.
- Special arrestors protect from acid corrosion & spark.
- Long shelf life, complete Maintenance Free, Fit & Forget.
- World class components and advanced Technology

GULFRACER™ GOLD

Every single GULFRACER™ GOLD battery is developed employing advanced technology and state-of-the-art components. These maintenance-free batteries have a long life and offer consistent power for extended duration of time. Like all of our batteries, GULFRACER™ GOLD benefits from our high customer service standards.



JIS RANGE for Passenger car, Utility vehicles, light & commercial vehicles and for heavy duty commercial vehicles

Battery Type		Ref. Capacity (Ah)	CCA (A) SAE-18°C	Dimension (mm)				Terminal Layout	Terminal Size	Holdown
Nomenclature	OLD JIS NO			L	W	H	TH			
MF 32B20R/L	NS40	32	280	195	127	199	223	1/0	B	B0
MF 36B20R/L	NS40Z	35	310	195	127	199	223	1/0	B	B0
MF 36B20RS/LS	NS40ZS	35	310	195	127	199	223	1/0	A	B0
MF 46B24R/L	N40	40	320	235	127	199	223	1/0	A	B0
MF 55B24R/L	NS60	45	360	235	127	199	223	1/0	B	B0
MF 55B24RS/LS	NS60(S)	45	360	235	127	199	223	1/0	A	B0
MF 55D23R/L	-	60	450	230	171	202	223	1/0	A	B1
MF 75D23R/L	-	65	475	230	171	202	223	1/0	A	B1
MF 48D26R/L	N50	50	375	260	172	204	224	1/0	A	B0
MF 55D26R/L	N50Z	60	450	260	172	204	224	1/0	A	B0
MF 75D26R/L	-	65	450	260	172	204	224	1/0	A	B0
MF 80D26R/L	-	70	525	260	172	204	224	1/0	A	B1
MF 95D26R/L	-	75	555	260	172	204	224	1/0	A	B1
MF 65D31R/L	N70	70	525	303	172	199	222	1/0	A	B0
MF 75D31R/L	N70Z	75	565	303	172	199	222	1/0	A	B0
MF 95D31R/L	NS100	85	620	303	172	199	222	1/0	A	B0
MF 105D31R/L	-	90	655	303	172	199	222	1/0	A	B0
MF 95E41R/L	N100	100	525	404	170	210	236	1/0	A	B0
MF 115F51R/L	N120	120	700	502	178	208	234	3/4	A	B0
MF 145G51R/L	N150	150	850	506	223	212	238	3/4	A	B0
MF 190H52R/L	N200	200	1000	518	274	215	240	3/4	A	B0



DIN RANGE for Passenger car, Utility vehicles, light & commercial vehicles and for heavy duty commercial vehicles

MF 54434/59	-	44	450	206	175	190	190	0	A	B3
MF 54519	-	45	460	242	175	175	175	0	A	B4
MF 55530/59/48/65	-	55	420	242	174	190	190	1/0	A	B3
MF 56219/21	-	62	500	242	174	190	190	1/0	A	B3
MF 56618/38	-	66	550	276	175	190	190	0	A	B3
MF 57412	-	74	600	276	175	190	190	0	A	B3
MF 58043	-	80	650	315	175	190	190	0	A	B3
MF 58815/27	-	88	700	353	175	190	190	0	A	B3
MF 60038	-	100	800	353	175	190	190	0	A	B3
MF 62523	-	125	750	280	267	207	230	5	A	B0
MF 64020	-	140	850	513	189	195	222	3	A	B3
MF 67018	-	170	1080	513	223	195	223	3	A	B0
MF 68032	-	180	1100	513	223	195	223	3	A	B0
MF 70027 /29	-	200	1200	518	274	215	240	3/4	A	B0
MF 73027/29	-	230	1500	518	274	215	240	3/4	A	B0

AMERICAN RANGE for Passenger car, Utility vehicles, light & commercial vehicles and for Marine Vehicles

MF 78-72	-	60	570	260	181	182	182	1	ST	B7
MF 65-72	-	90	720	306	189	170	192	1	A	B1
MF 74-60	-	60	525	260	181	204	204	1	ST	B0
MF 34-60	-	55	520	260	172	182	202	1	A	B0
MF 31-12	-	115	860	339	174	200	220	0	TH	B0
MF 27-12	-	90	600	303	172	199	222	1	DT	B0

Layout



Terminal Details

Terminal Type	Positive (mm)	Negative (mm)
B	14.7 ⁰ _{0.3-}	13.0 ⁰ _{0.3-}
A	19.5 ⁰ _{0.3-}	17.9 ⁰ _{0.3-}

Confirms to JIS D5301:1999 and DIN standards. The CCA values are at service gravity 1.280±0.01 at 27°C
All GULFRACER™ Gold batteries are fitted with Charge status Indicator and available in Red & Black container.

Contact Us

For more information about Reem's Hybrid, Dry Charged Batteries or any of our other products and services, please get in touch – we would be delighted to hear from you:

Reem Batteries &
Power Appliances Co. SAOC

Head Office & Factory:
P.O. Box 3

Maxis International Trading | +974 7704 4848
Retaj Building, Salwa Road, Doha, Qatar
info@maxisinternationaltrading.com